



Smeermiddelenindustrie • Schmiermittelindustrie

DE OLIEBRON LUBRICATION(GD) CO.,LTD

TEL: +86 4008801150

Internet: <http://www.deoliebron.com>

E-mail: info@deoliebron.com

Lube-oil industry • Industrie Lubrifiant

HyperSynth 0W20

Description

A fuel economy SAE 0W20 motor oil, developed according the most recent technology, based on specially selected synthetic base oils and a well balanced choice of advanced additives to obtain the following properties:

- a high fuel economy
- a high and stable viscosity index
- a good resistance against shearing
- a very fast cold start, even at very low temperatures
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion power
- a very strong protection against wear, corrosion and foaming

Application

A fuel economy, specially formulated engine oil suitable for petrol and diesel engines of Volvo cars where the manufacturer prescribes a product that meets the specification VCC RBS0-2AE with viscosity SAE 0W20.

Specifications

API SP
ILSAC
GF-6a
Honda·Hyundai·KIA·Mazda
Mitsubishi Dia Queen
Nissan·Toyota

Typicals

Density at 20 °C, kg/l	0,844
Viscosity -35 °C, mPa.s	5045
Viscosity 40 °C, mm ² /s	43,33
Viscosity 100 °C, mm ² /s	8,256
Viscosity Index	169
Flash Point COC, °C	230
Pour Point, °C	-42
Total Base Number, mgKOH/g	8,15
Sulphate Ash, %	0,79
HTHS viscosity@150, mPa.s	2,8