



Smeermiddelenindustrie • Schmiermittelindustrie

Lube-oil industry • Industrie Lubrifiant

DE OLIEBRON LUBRICATION(GD) CO.,LTD

TEL: +86 4008801150

Internet: <http://www.deoliebron.com>

E-mail: info@deoliebron.com

HyperSynth 5w30

Description

This sophisticated full-synthetic fuel economy universal motor oil is produced with high quality synthetic base oils with a high viscosity index and a well-balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application

This universal fuel economy synthetic motor oil is recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with the specifications as stated below.

Specifications

Performance level:
API SP

Typicals

Density at 20°C, kg/l	0,847
Viscosity -30 °C, mPa.s	5980
Viscosity 40 °C, mm ² /s	65,23
Viscosity 100 °C, mm ² /s	11,00
Viscosity Index	148
Flash Point COC, °C	230
Pour Point, °C	-38
Total Base Number, mgKOH/g	7,15
Sulphate Ash, %	0,76
HTHS viscosity@150, mPa.s	3,5